

Client:	BIO - INCUBATOR, DEPT OF BIO TECH, IIT, Madras.	
Project:	PROPOSED INTERIORS FOR BIO - INCUBATOR @ IITMRP & IIT, Madras.	
Location:	3rd FLOOR @ IITMRP & 2nd FLOOR @ IIT, Madras.	
B.O.Q	B.O.Q FOR SUPPLY OF CHAIRS	
Architects:	VARSHA & PRADEEP ARCHITECTS	

S.No.	Item Description	Qty			Unit	Rate	Amount			Image
		IITMRP	IIT,M	TOTAL			IITMRP	IIT,M	TOTAL	

A Workstation Chairs- Swift MB										
	Back Frmae	(ABS Back Frame)	19	15	34	NOS				
	Arm rest	Adjustable Arms								
	Mechansim	Synchro tilting with Multilocking								
	Lumbar Support	ABS Spring Type Lumabr Support								
	Seat	Moulded cushion as per ergonomical and contoured designs, density range of 45- 55 Kgs per cubic meter								
	Seat Inner	ABS- Arco Nitrite Butadiene Styrene(No Plywood)								
	Gas lift	Heavy Duty Chair Cylinder Part Pneumatic Gas Height Adjustment Lift. Load capacity of up to 160 Kgs. It's a class 4 (thicker walls than standard class 3) with 450n rating. (a standard pneumatic gas cylinder has a 300n rating)								
	Metal parts	They are made of CRCA and mild steel and powder coated with epoxy polymer to a thickness of 4-45 microns								
	Base	Nylon Five prong injection moulded in polyamide polymer with 30% glass reinforcement. Top surface textured for scratch resistance, BIFMA standard to withstand static load of 1100 Kg with minimum deflection at center, honeycomb rubbing pattern on underside provided to prevent torsional deflection								
	Twin wheel castors	Twin wheel castors with smooth rolling action with kingpin ring locking arrangement to snap fit on moulded base and each castor weight tolerance is 80 Kgs								



B Meeting room chairs- Brixton MB										
	Back Frmae	(ABS Back Frame)	6.0	6.0	12.0	NOS				
	Arm rest	Adjustable Arms								
	Mechansim	Synchro tilting with Multilocking								
	Lumbar Support	SpringType Lumbar support and Up& down Movement								
	Seat	Moulded cushion as per ergonomical and contoured designs, density range of 45- 55 Kgs per cubic meter								
	Seat Inner	ABS- Arco Nitrite Butadiene Styrene(No Plywood)								



Gas lift	Heavy Duty Chair Cylinder Part Pneumatic Gas Height Adjustment Lift. Load capacity of up to 160 Kgs. It's a class 4 (thicker walls than standard class 3) with 450n rating. (a standard pneumatic gas cylinder has a 300n rating)
Metal parts	They are made of CRCA and mild steel and powder coated with epoxy polymer to a thickness of 4--45 microns
Base	Nylon Five prong injection moulded in polyamide polymer with 30% glass reinforcement. Top surface textured for scratch resistance, BIFMA standard to withstand static load of 1100 Kg with minimum deflection at center, honeycomb rubbing pattern on underside provided to prevent torsional deflection
Twin wheel castors	Twin wheel castors with smooth rolling action with kingpin ring locking arrangement to snap fit on moulded base and each castor weight tolerance is 80 Kgs



	C LAB STOOLS -Bar-Fab	32.0	2.0	34.0	NOS				
	Pu seat & back, Gaslift for height adjustment, SS footrest - ring type, Five prong base with castors								
	D LOUNGE CHAIRS in Reception	2.0	2.0	4.0	NOS				
	Providing and placing Lounge chairs. Structure of the chair to be made with SS framework and finished with leatherite as per approved sample and colour. (Refer image).								
	E TEA TABLE in Reception	1.0	1.0	2.0	NOS				
	Providing and placing Tea table 400x400x400. Base made with brushed SS tubes 32 dia and tied at 1 level with 25mm dia tubes. Top made of 12mm toughened glass fixed with ss studs and imported transparent glue.								
		GRAND TOTAL							
		TAX							
		GRAND TOTAL (INCLUSIVE OF TAX)							