

	<p>भारतीय प्रौद्योगिकीसंस्थानमद्रासचेन्नै 600 036  <b>INDIAN INSTITUTE OF TECHNOLOGY MADRAS Chennai 600 036</b>  भंडार एवं क्रय अनुभाग  <b>STORES &amp; PURCHASE SECTION</b>  Email: <a href="mailto:adstores@iitm.ac.in">adstores@iitm.ac.in</a>  दूरभाष: (044) 2257 8285 / 8286 / 8287 / 8288 फ़ैक्स: (044) 2257 8292  Telephone : (044) 2257 8285/8286/8287/8288 FAX: (044) 2257 8292  GSTIN: 33AAAAI3615G1Z6</p>	
---	--	---

**BOOMA SOWRIRAJAN**

*Assistant Registrar (Stores & Purchase)*

**Date: 19.05.2021**

**CORRIGENDUM - VIII**

**“SUPPLY, INSTALLATION AND COMMISSIONING OF AUDIO AND VIDEO CONFERENCING SYSTEM  
IN BOARD ROOM of IIT MADRAS AS PER DESIGN”**

Tender No. IITM/SPS/AV System/001/2021-22

e-Tender ID: 2021\_IITM\_75180\_1

**1. In Page No. 10, (C) – Bill of Material – Sl. No. 6 may be read as**

Sl.No	Description	Make	UoM	Qty
6	<b>48 / 52 port Layer 3 Managed 1 or above Gigabit Switch</b>	<b>CISCO/EXTREME/HPE</b>	No.	1
<b>Instead of</b>				
6	52 port Layer 3 Managed 1 or above Gigabit Switch	CISCO/EXTREME	No.	1

**2. In Page No. 15&16, (D) – Detailed Technical Specification – Sl. No. 6 – 52 port Layer 3 Managed 1 or above Gigabit Switch may be read as**

Item Reference	6
Item Description	<b>48 / 52 port Layer 3 Managed 1 or above Gigabit Switch</b>
Make/Brand	<b>CISCO/EXTREME/HPE</b>
Minimum Performance Parameters	
USB slot	
Spanning Tree Protocol	Standard 802.1d Spanning Tree support; Fast convergence using 802.1w (Rapid Spanning Tree [RSTP]), enabled by default; 8 instances should be supported; Multiple Spanning Tree instances using 802.1s (MSTP)
Port grouping	Support for IEEE 802.3ad Link Aggregation Control Protocol (LACP) <ul style="list-style-type: none"> <li>● Up to 8 groups</li> <li>● Up to 8 ports per group with 16 candidate ports for each (dynamic) 802.3ad link aggregation</li> </ul>
Multicast TV VLAN	Multicast TV VLAN allows the single multicast VLAN to be shared in the network while subscribers remain in separate VLANs (also known as MVR)
Secure Shell (SSH) Protocol	SSH is a secure replacement for Telnet traffic. SCP also uses SSH. SSH v1 and v2 are supported
Web user interface	Built-in switch configuration utility for easy browser-based device configuration (HTTP/HTTPS). Supports configuration, system dashboard, system maintenance, and monitoring.
<b>Instead of</b>	
Item Reference	6
Item Description	52 port Layer 3 Managed 1 or above Gigabit Switch

Make/Brand	CISCO/EXTREME
Minimum Performance Parameters	
USB slot	
Spanning Tree Protocol	Standard 802.1d Spanning Tree support; Fast convergence using 802.1w (Rapid Spanning Tree [RSTP]), enabled by default; 8 instances should be supported; Multiple Spanning Tree instances using 802.1s (MSTP)
Port grouping	Support for IEEE 802.3ad Link Aggregation Control Protocol (LACP) <ul style="list-style-type: none"> <li>Up to 8 groups</li> <li>Up to 8 ports per group with 16 candidate ports for each (dynamic) 802.3ad link aggregation</li> </ul>
Multicast TV VLAN	Multicast TV VLAN allows the single multicast VLAN to be shared in the network while subscribers remain in separate VLANs (also known as MVR)
Secure Shell (SSH) Protocol	SSH is a secure replacement for Telnet traffic. SCP also uses SSH. SSH v1 and v2 are supported
Web user interface	Built-in switch configuration utility for easy browser-based device configuration (HTTP/HTTPS). Supports configuration, system dashboard, system maintenance, and monitoring.
Power	740 W Dedicated PoE Power

**3. In Page No. 52 – Proforma Format for Financial Bid (BOQ) Format - Sl. No. 6 may be read as**

Sl.No	Description	Qty	UoM	Rate per unit	Total cost without Tax	GST	Total cost with tax
6	<b>48 / 52 port Layer 3 Managed 1 or above Gigabit Switch</b>	1	No.				
<b>Instead of</b>							
6	52 port Layer 3 Managed 1 or above Gigabit Switch	1	No.				

**NOTE:**

- Further request if any received from the bidders for an amendment will not be considered.
- BOQ not able to update due to process started for bid submission.

**All other conditions remain unchanged.**

Sd/-  
Assistant Registrar (Stores & Purchase)