

LINE INTERACTIVE UPS OF 650VA CAPACITY WITH QUASI SINE WAVE OUTPUT

TECHNICAL SPECIFICATIONS

I. Test

- | | | | |
|----|---|---|----------------------|
| 1. | Input AC Voltage | : | 165V-265 V |
| 2. | Buck and Boost operation | : | ± 12% |
| 3. | Output Voltage (Battery Mode) | : | 230V ± 8% |
| 4. | Output frequency (Battery Mode) | : | 50Hz ± 0.5% |
| 5. | Transfer Time (Mains to Battery and Battery to Mains) | : | < 5ms |
| 6. | Capacity (in Watts) | : | >360W |
| 7. | (i) Backup time on Full Load in Battery Mode | : | >5 minutes |
| | (ii) Battery Energy Storage capacity (with original new SMF lead acid Batteries*) | : | >84 Whr |

II. Other Requirements

- | | | |
|-----|---|-------------------|
| 1. | Temperature and Humidity | |
| | i) Operating Temperature Range | : upto 40°C |
| | ii) Humidity | : upto 95% Rh |
| 2. | Noise level (at 1 meter) | : < 50dB |
| 3. | Conformance to Standards | |
| | i) EMC Standards | : IEC 801-2,3,4,5 |
| | ii) Emission Standard | : EN55022 Class B |
| | iii) Safety Standard | : EN50091-1 |
| 4. | Cold start feature at full load | : |
| 5. | Standard hardware / software support for serial communication interface | : |
| 6. | Free Software Package for advanced UPS Power Management and Diagnostics | : |
| 7. | Protection features including lightning and surge protection | : |
| 8. | Network grade line conditioning to prevent glitches | : |
| 9. | Intelligent Battery Management Feature | : |
| 10. | Three years Warranty Period for UPS and Battery | : |

<p>*Provide the batteries of SMF type from the following manufacturer i.e Hitachi, Panasonic, Global Yuasa, Yuasa, Exide, CSB or Amar Raja</p>
--

LINE INTERACTIVE UPS OF 1000VA CAPACITY WITH QUASI SINE WAVE OUTPUT

TECHNICAL SPECIFICATIONS

I. Test

- | | | | |
|----|---|---|-----------------|
| 1. | Input AC Voltage | : | 175V-275 V |
| 2. | Buck and Boost operation | : | 12% |
| 3. | Output Voltage (Battery Mode) | : | 230V \pm 8% |
| 4. | Output frequency (Battery Mode) | : | 50Hz \pm 0.5% |
| 5. | Transfer Time (Mains to Battery and Battery to Mains) | : | < 5ms |
| 6. | Capacity (in Watts) | : | >600W |
| 7. | (i) Backup time on Full Load in Battery Mode | : | >5 minutes |
| | (ii) Battery Energy Storage capacity (with original new SMF lead acid Batteries*) | : | >216 Whr |

II. Other Requirements

- | | | |
|-----|---|-------------------|
| 1. | Temperature and Humidity | |
| | i) Operating Temperature Range | : Upto 40°C |
| | ii) Humidity | : Upto 95% Rh |
| 2. | Noise level (at 1 meter) | : < 50dB |
| 3. | Conformance to Standards | |
| | i) EMC Standards | : IEC 801-2,3,4,5 |
| | ii) Emission Standard | : EN55022 Class B |
| | iii) Safety Standard | : EN50091-1 |
| 4. | Cold start feature at full load | : |
| 5. | Standard hardware / software support for serial communication interface | : |
| 6. | Free Software Package for advanced UPS Power Management and Diagnostics | : |
| 7. | Protection features including lightning and surge protection | : |
| 8. | Network grade line conditioning to prevent glitches | : |
| 9. | Intelligent Battery Management Feature | : |
| 10. | Three years Warranty Period for UPS and Battery | : |

<p>*Provide the batteries of SMF type from the following manufacturer i.e Hitachi, Panasonic, Global Yuasa, Yuasa, Exide, CSB or Amar Raja</p>
--

LINE INTERACTIVE UPS OF 1000VA CAPACITY WITH SINE WAVE OUTPUT

TECHNICAL SPECIFICATIONS

I. Test

- | | | | |
|----|---|---|-----------------|
| 1. | Input AC Voltage | : | 175V-275 V |
| 2. | Buck and Boost operation | : | 12% |
| 3. | Output Voltage (Battery Mode) | : | 230V \pm 8% |
| 4. | Output frequency (Battery Mode) | : | 50Hz \pm 0.5% |
| 5. | Transfer Time (Mains to Battery and Battery to Mains) | : | < 6ms |
| 6. | Capacity (in Watts) | : | >600W |
| 7. | (i) Backup time on Full Load in Battery Mode | : | >5 minutes |
| | (ii) Battery Energy Storage capacity (with original new SMF lead acid Batteries*) | : | >168 Whr |

II. Other Requirements

- | | | |
|-----|---|-------------------|
| 1. | Temperature and Humidity | |
| | i) Operating Temperature Range | : Upto 40°C |
| | ii) Humidity | : Upto 95% Rh |
| 2. | Noise level (at 1 meter) | : < 50dB |
| 3. | Conformance to Standards | |
| | i) EMC Standards | : IEC 801-2,3,4,5 |
| | ii) Emission Standard | : EN55022 Class B |
| | iii) Safety Standard | : EN50091-1 |
| 4. | Cold start feature at full load | : |
| 5. | Standard hardware / software support for serial communication interface | : |
| 6. | Free Software Package for advanced UPS Power Management and Diagnostics | : |
| 7. | Protection features including lightning and surge protection | : |
| 8. | Network grade line conditioning to prevent glitches | : |
| 9. | Intelligent Battery Management Feature | : |
| 10. | Three years Warranty Period for UPS and Battery | : |

*Provide the batteries of SMF type from the following manufacturer i.e Hitachi, Panasonic, Global Yuasa, Yuasa, Exide, CSB or Amar Raja

LINE INTERACTIVE UPS OF 1500VA CAPACITY WITH SINE WAVE OUTPUT

TECHNICAL SPECIFICATIONS

I. Test

- | | | | |
|----|---|---|-----------------|
| 1. | Input AC Voltage | : | 175V-275 V |
| 2. | Buck and Boost operation | : | 12% |
| 3. | Output Voltage (Battery Mode) | : | 230V \pm 8% |
| 4. | Output frequency (Battery Mode) | : | 50Hz \pm 0.5% |
| 5. | Transfer Time (Mains to Battery and Battery to Mains) | : | < 6ms |
| 6. | Capacity (in Watts) | : | >900W |
| 7. | (i) Backup time on Full Load in Battery Mode | : | >5 minutes |
| | (ii) Battery Energy Storage capacity (with original new SMF lead acid Batteries*) | : | >216 Whr |

II. Other Requirements

- | | | |
|-----|---|-------------------|
| 1. | Temperature and Humidity | |
| | i) Operating Temperature Range | : Upto 40°C |
| | ii) Humidity | : Upto 95% Rh |
| 2. | Noise level (at 1 meter) | : < 50dB |
| 3. | Conformance to Standards | |
| | i) EMC Standards | : IEC 801-2,3,4,5 |
| | ii) Emission Standard | : EN55022 Class B |
| | iii) Safety Standard | : EN50091-1 |
| 4. | Cold start feature at full load | : |
| 5. | Standard hardware / software support for serial communication interface | : |
| 6. | Free Software Package for advanced UPS Power Management and Diagnostics | : |
| 7. | Protection features including lightning and surge protection | : |
| 8. | Network grade line conditioning to prevent glitches | : |
| 9. | Intelligent Battery Management Feature | : |
| 10. | Three years Warranty Period for UPS and Battery | : |

*Provide the batteries of SMF type from the following manufacturer i.e Hitachi, Panasonic, Global Yuasa, Yuasa, Exide, CSB or Amar Raja

TECHNICAL SPECIFICATIONS

1kVA UPS True On Line, Sine wave Output

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 180V-270V AC
2. Input Power Factor @ F.L : > 0.95
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required	
	36V Bus	48V Bus
For 30 min	> 864 Watt Hr	> 864 Watt Hr
For 60 min	> 1440 Watt Hr	> 1440 Watt Hr

5. AC Output Voltage and steady state Regulation @ FL : 230V AC; better than \pm 1%
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : > 800W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 80%
 - (ii) Mains mode : > 80%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

2kVA UPS True On Line, Sine wave Output

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 170V-270V AC
2. Input Power Factor @ F.L : > 0.95
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required	
	48 V Bus	72 / 96 V Bus
For 30 min	> 2016 Watt Hr	> 2304 Watt Hr
For 60 min	> 3120 Watt Hr	> 3648 Watt Hr

5. AC Output Voltage and steady state Regulation @ FL : 230V AC; better than \pm 1%
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : > 1600W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 80%
 - (ii) Mains mode : > 80%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

3kVA UPS True On Line, Sine wave Output

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 170V-270V AC
2. Input Power Factor @ F.L : > 0.95
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required	
	96 V Bus	192 V Bus
For 30 min	> 2880 Watt Hr	> 2880 Watt Hr
For 60 min	> 6240 Watt Hr	> 4608 Watt Hr

5. AC Output Voltage and steady state Regulation @ FL : 230V AC; better than \pm 1%
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : > 2400W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 83%
 - (ii) Mains mode : > 85%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

5kVA UPS True On Line, Sine wave Output

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 180V-270 V AC
2. Input Power Factor @ F.L : > 0.95
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required
	192 V Bus
For 30 min	> 4608 Watt Hr
For 60 min	> 7680 Watt Hr

5. AC Output Voltage and steady state Regulation @ FL : 230V AC; better than \pm 1%
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : >4000W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 87%
 - (ii) Mains mode : > 85%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

10kVA UPS True On Line, Sine wave Output (3 Ø i/p & 1 Ø o/p)

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 374V-506 V AC
2. Input Power Factor @ F.L : > 0.95
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required
	240 V Bus
For 30 min	> 9600 Watt Hr
For 60 min	> 15600 Watt Hr

5. AC Output Voltage and steady state Regulation @ FL : 230V AC; better than \pm 1%
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : > 8000W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 84%
 - (ii) Mains mode : > 89%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

10kVA UPS True On Line, Sine wave Output (1 Ø i/p & 1 Ø o/p)

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 180V-270 V AC
2. Input Power Factor @ F.L : > 0.95
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required
	240 V Bus
For 30 min	> 9600 Watt Hr
For 60 min	> 15600 Watt Hr

5. AC Output Voltage and steady state Regulation @ FL : 230V AC; better than \pm 1%
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : > 8000W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 84%
 - (ii) Mains mode : > 89%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

15kVA UPS True On Line, Sine wave Output (3 Ø i/p & 1 Ø o/p)

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 415V \pm 15%
2. Input Power Factor @ F.L : > 0.93
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required
	240 V Bus
For 30 min	> 15600 Watt Hr
For 60 min	> 24000 Watt Hr

5. AC Output Voltage and steady state Regulation @ FL : 230V AC; better than \pm 1%
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : > 12000W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 84%
 - (ii) Mains mode : > 89%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

15kVA UPS True On Line, Sine wave Output (3 Ø i/p & 3 Ø o/p)

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 415V \pm 15%
2. Input Power Factor @ F.L : > 0.93
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required
	240 V Bus
For 30 min	> 15600 Watt Hr
For 60 min	> 24000 Watt Hr

- 5 a. AC Output Voltage and steady state Regulation @ FL : 415V AC; < 1% (for balanced load)
< 2% (for 100% unbalanced load)
- 5 b. Phase displacement : < 1° (for balanced load)
< 2° (for 100% unbalanced load)
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : > 12000W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 84%
 - (ii) Mains mode : > 89%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

20kVA UPS True On Line, Sine wave Output (3 Ø i/p & 1 Ø o/p)

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 415V \pm 15%
2. Input Power Factor @ F.L : > 0.95
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required
	240 V Bus
For 30 min	> 15600 Watt Hr
For 60 min	> 24000 Watt Hr

5. AC Output Voltage and steady state Regulation @ FL : 230V AC; better than \pm 1%
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : >16000W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 84%
 - (ii) Mains mode : > 89%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

20kVA UPS True On Line, Sine wave Output (3 Ø i/p & 3 Ø o/p)

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 415V \pm 15%
2. Input Power Factor @ F.L : > 0.95
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required
	240 V Bus
For 30 min	> 15600 Watt Hr
For 60 min	> 24000 Watt Hr

- 5 a. AC Output Voltage and steady state Regulation @ FL : 415V AC; < 1% (for balanced load)
< 2% (for 100% unbalanced load)
- 5 b. Phase displacement : < 1° (for balanced load)
< 2° (for 100% unbalanced load)
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : > 16000W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 84%
 - (ii) Mains mode : > 89%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

30kVA UPS True On Line, Sine wave Output (3 Ø i/p & 1 Ø o/p)

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 415V \pm 15%
2. Input Power Factor @ F.L : > 0.93
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required
	360 V Bus
For 30 min	> 28800 Watt Hr
For 60 min	> 46800 Watt Hr

5. AC Output Voltage and steady state Regulation @ FL : 230V AC; better than \pm 1%
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : > 24000W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 84%
 - (ii) Mains mode : > 89%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS

TECHNICAL SPECIFICATIONS

30kVA UPS True On Line, Sine wave Output (3 Ø i/p & 3 Ø o/p)

Technology:

PWM technology in True on-line operation, employing double conversion method using MOSFETs / IGBTs.

Method of Inversion:

Adaptive pulse width modulation or weighted pulse width modulation with high Frequency switching (>10 kHz for MOSFETs and >5kHz for IGBTs).

Test Parameters:

1. Input Voltage Range @ F.L : 415V \pm 15%
2. Input Power Factor @ F.L : > 0.93
3. Input Frequency Variation : 50 Hz \pm 5%
4. Total Energy storage capacity of Battery (in one string) @ F.L and @ Non-A/C environment

Backup time	Watt Hr. required
	360 V Bus
For 30 min	> 28800 Watt Hr
For 60 min	> 46800 Watt Hr

- 5 a. AC Output Voltage and steady state Regulation @ FL : 415V AC; < 1% (for balanced load)
< 2% (for 100% unbalanced load)
- 5 b. Phase displacement : < 1° (for balanced load)
< 2° (for 100% unbalanced load)
6. Transient Voltage Regulation at Step Load : < 5%
7. Maximum deliverable continuous Output Power : > 24000W
8. Output Frequency : 50 Hz \pm 4% (Synchronous to mains)
50 Hz \pm 0.5% (Free running)
9. Efficiency
 - (i) Battery mode : > 84%
 - (ii) Mains mode : > 89%
10. THD @ F.L : < 3% (for linear load);
< 5% (for nonlinear load)
11. Crest Factor @ F.L : > 3 : 1
12. Over Load Duration @ 110%, 125% and 150% of F.L : 5 min, 1 min and 2 sec respectively
13. Static bypass switch: Bi-directional with change over time less than 10 milliseconds in free running mode and instantaneous in synchronous mode from Inverter to Bypass and vice-versa.
14. Temperature and Humidity
 - (i) Operating Temperature Range : upto 40°C
 - (ii) Humidity : upto 95% Rh
15. Noise level (at 1 meter) : < 45 dB
16. Conformance to Standards
 - (i) EMC Standards : IEC 801 - 2,3,4,5
 - (ii) Emission Standard : EN55022 Class B
 - (iii) Safety Standard : EN 50091-1

Battery Charger Operation:

Float-cum-boost charger with automatic boost/trickle charger modes with current limiting features. It's characteristics shall be such as to match the float/ boost charging of the batteries as per battery characteristic, for battery life enhancement. High frequency chargers preferred.

Protection Features:

- a) Isolation - Output shall be fully isolated from mains and with surge /spike suppressors incorporated.
- b) Current limiting, over load and Short circuit protection.
- c) Phase locking mechanism with mains frequency.
- d) Over voltage / Under voltage protection.
- e) All other protection systems as required for safety of the system.

Other Features:

- 1. Cold start feature under full load condition.
- 2. Standard hardware / software support for serial communication interface and SNMP / Web monitoring.
- 3. Auto shut down and energy saving features.
- 4. Temperature compensated battery charging for battery life enhancement.
- 3. Automated battery testing and advanced battery management features.
- 4. Sufficient ventilation and forced air cooling through fans.
- 5. Documentation/Manuals support for component level Servicing.
- 6. Serviceability at component level.
- 7. Spares and accessories deliverable along with UPS for Servicing.

Warranty and AMC:

- 1. 3 years Warranty Period for UPS as well as Batteries.
- 2. Comprehensive AMC covering the batteries, after the expiry of warranty period for the configurations

(i) to (iv) given below.

Important instructions:

- a) Separate quote is invited for each one of the following configurations:
 - (i) with built- in isolation transformer and 30 minutes back up time.
 - (ii) with built- in isolation transformer and one hour back up time.
 - (iii) with external isolation transformer and 30 minutes back up time.
 - (iv) with external isolation transformer and one hour back up time.
- b) Batteries must be SMF type of following make:
Hitachi, Panasonic, Global Yuasa, Yuasa, Base or Rocket.
- c) Quote should indicate the Model/Series Name and Model Number of UPS