

Corrigendum 1

Ref No.GTB10/MANU/IOE23/10/LSCC

Corrigendum: Laboratory Scale Aggregate Cone Crusher

	Item No.	Original Specification	Revised Specification
General	1	It must be fully automatic (close circuit) and capable of breaking rocks/stones/aggregates into smaller fractions having varying grain size distribution between 3 mm to 0 mm in a single cycle of crushing	It must be fully automatic (close circuit) and capable of breaking rocks/stones/aggregates into smaller fractions having varying grain size distribution between 2 mm to 0 mm in a single cycle of crushing
Technical	5	Aggregate feed size shall not be smaller than 19 mm	Aggregate feed size shall not be smaller than 12 mm
	6	The machine must be capable of breaking rocks/stones/aggregates into smaller fractions between 3 mm to 0 mm in a single cycle of crushing	The machine must be capable of breaking rocks/stones/aggregates into smaller fractions between 2 mm to 0 mm in a single cycle of crushing
	7	The outlet size from which the crushed aggregates will be coming (i.e. grinding fineness) must be adjustable to at least 5 settings	The outlet size from which the crushed aggregates will be coming (i.e. grinding fineness) must be adjustable to at least 2 settings
	12	The machine must come with a separate dust extraction port	To be deleted
	14	The power of the motor shall be at least 3 HP	The power of the motor shall be at least 2 HP
	15	CE certificate must be supplied	To be deleted
Accessories		All the accessories required for safely operating this equipment shall be provided. Any other optional accessories, other than those mentioned below, suitable for the system may also be quoted.	All the accessories required for safely operating this equipment shall be provided. Any other optional accessory suitable for the system may also be quoted.
Accessories	1	Dust extraction port	Dust extraction port (optional)
	2	2 drawers for crushed aggregates collection	2 drawers for crushed aggregates collection (optional)
	3	Machine stand	Machine stand (optional)
	4	Cleaning accessories	Cleaning accessories (optional)
	5	Electric box with overload protection	Electric box with overload protection (optional)
Warranty		3 years	1 year