

#### INDIAN INSTITUTE OF TECHNOLOGY MADRAS Chennai 600 036

Telephone: [044] 2257 9763 E-mail: tender@imail.iitm.ac.in



Date: 07.02.2023

The Manager (Project Purchase)

Open Tender Reference No: CY/PRAD/05/IOE23/GLOVEBOX

GEM NAR ID: GEM/GARPTS/29112022/IO5GHQ5VW7P0 Due Date/Time: 20.02.2023@ 3:00 PM

Dear Sir/Madam,

On behalf of the Indian Institute of Technology Madras, Tenders are invited in two bid system from Class-I local suppliers and Class II local suppliers, for the supply of "GLOVE BOX" Conforming to the specifications given in Annexure -A.

Tender Documents may be downloaded from Central Public Procurement Portal <a href="https://etenders.gov.in/eprocure/app">https://etenders.gov.in/eprocure/app</a>. Aspiring Bidders who have not enrolled / registered in e-procurement should enroll / register before participating through the website <a href="https://etenders.gov.in/eprocure/app">https://etenders.gov.in/eprocure/app</a>. The portal enrolment is free of cost. Bidders are advised to go through instructions provided at "Help for contractors". [Special Instructions to the Contractors/Bidders for the e-submission of the bids online through this eProcurement Portal"]

Bidders can access tender documents on the website (For searching in the NIC site, kindly go to Tender Search option and type 'IIT'. Thereafter, click on "GO" button to view all IIT Madras tenders). Select the appropriate tender and fill them with all relevant information and submit the completed tender document online on the website <a href="https://etenders.gov.in/eprocure/app">https://etenders.gov.in/eprocure/app</a> as per the schedule attached.

	Pre-bid Meeting	:	NA
<u>1)</u>	Details		
2)	ICCD V		TO THE TAX ASSESSED AND ASSESSED ASSESSED AND ASSESSED ASSESSED AND ASSESSED AND ASSESSED ASSE
<u>2)</u>	ICSR Vendor	:	<u>Vendor registration code</u> . Vendor registration with IC&SR (IITM) is mandatory for
	Registration		bidders to participate in tenders.
			** For Vendor Registration & Guidelines, Please follow the website:  https://icandsr.iitm.ac.in/vendorportal; Helpdesk: vendorhelpdesk@icsrpis.iitm.ac.in

<u>No manual bids will be accepted.</u> All tender documents including Technical and Financial bids should be submitted in the E-procurement portal.

Last date for receipt of tender	:	20.02.2023 @ 3:00 PM
Date & time of opening of tender	:	21.02.2023 @ 3:00 PM

# 3. Instructions to the Bidder:

A) Searching for tender documents		<ul> <li>There are various search options built in the CPP Portal, to facilitate bidders to search active tenders by several parameters. These parameters could include Tender ID, organization name, location date, value, etc. There is also an option of advanced search for tenders, wherein the bidders may combine a number of search parameters such as organization name, form of contract, location date, other keywords etc. to search for a tender published on the CPP Portal.</li> <li>Once the bidders have selected the tenders they are interested in they may download the required documents / tender schedules. These tenders can be moved to the respective "My Tender" folder. This would enable the CPP Portal to intimate the bidders through SMS / email in case there is any corrigendum issued to the tender document.</li> <li>The bidder should make a note of the unique Tender ID assigned to each tender, in case they want to obtain any clarification / help.</li> </ul>		
<u>B)</u>	Assistance to bidders	<ul> <li>Any queries relating to the tender document and the terms an conditions contained therein should be addressed to the Tende Inviting Authority for a tender or the relevant contact perso indicated in the tender.</li> <li>Any queries relating to the process of online bid submission of queries relating to CPP Portal in general may be directed to the</li> </ul>		
<u>C)</u>	Enrollment Process	24x7 CPP Portal Helpdesk. The contact number for the helpdesk is [0120-4200462, 0120-4001002, 0120-4001005]  REGISTRATION		
	to Bidders	<ul> <li>Bidders are required to enroll on the e-Procurement module of the Central Public Procurement Porta URL:https://etenders.gov.in/eprocure/app by clicking of "Online Bidder Enrollment". Enrollment on the CPP Portal if free of charge.</li> <li>As part of the enrolment process, the bidders will be required to choose a unique username and assign a password for the accounts.</li> <li>Bidders are advised to register their valid email address an mobile numbers as part of the registration process. These would be used for any communication from the CPP Portal.</li> <li>Upon enrolment, the bidders will be required to register their valid Digital Signature Certificate (Class II or Class II Certificates with signing key usage) issued by any Certifyin Authority recognized by CCA India (e.g. Sify / TCS / nCode eMudhra etc.)</li> <li>Only one valid DSC should be registered by a bidder. Pleas note that the bidders are responsible to ensure that they do not lend their DSCs to others which may lead to misuse.</li> <li>Bidder then may log in to the site through the secured log-in be entering their user ID / password and the password of the DSC eToken.</li> <li>Possession of a Valid Class II/III Digital Signature Certificate</li> </ul>		

		(DSC) in the form of smart card/e-token in the company's name is a prerequisite for registration and participating in the bid submission activities through https://etenders.gov.in/eprocure/app  • Digital Signature Certificates can be obtained from the authorized certifying agencies, details of which are available in the web site https://etenders.gov.in/eprocure/app under the "Information about DSC".				
<u>D)</u>	Preparation of bids	:	Bidder should take into account any corrigendum published on the tender document before submitting their bids.			
			<ul> <li>Please go through the tender advertisement and the tender document carefully to understand the documents required to be submitted as part of the bid. Please note the number of covers in which the bid documents have to be submitted, the number of documents including the names and content of each of the document that need to be submitted. Any deviations from these may lead to rejection of the bid.</li> </ul>			
			<ul> <li>Bidder, in advance, should prepare the bid documents to be submitted as indicated in the tender document / schedule and generally shall be in PDF / XLS formats as the case may be. Bid documents may be scanned with 100 dpi with black and white option.</li> <li>To avoid the time and effort required in uploading the same set of standard documents which are required to be submitted as a part of every bid, a provision of uploading such standard documents (e.g. PAN card copy, GSTIN Details, annual reports, auditor certificates etc.) has been provided to the bidders. Bidders can use "My Documents" area available to them to upload such documents. These documents may be directly submitted from the "My Documents" area while submitting a bid, and need not be uploaded again and again. This will lead to a reduction in the time required for bid submission process.</li> </ul>			
<u>E)</u>	Submission of bids	•	• Bidder should log into the site well in advance for bid submission so that he/she can upload the bid in time i.e. on or before the bid submission date and time. Bidder will be responsible for any delay due to other issues.			
			The bidder has to digitally sign and upload the required bid documents one by one as indicated in the tender document.			
			Bidder has to select the bid security declaration. Otherwise, the tender will be summarily rejected.			
			• A standard BOQ format has been provided with the tender document to be filled by all the bidders. Bidders are requested to note that they should necessarily submit their financial bids in the format provided and no other format is acceptable. Bidders are required to download the BOQ file, open it and complete the detail with their respective financial quotes and other details (such as name of the bidder). If the BOQ file is found to be modified by the bidder, the bid will be rejected.			
			• The server time (which is displayed on the bidders' dashboard) will be considered as the standard time for referencing the deadlines for submission of the bids by the bidders, opening of bids etc. The			

		bidders should follow this time during bid submission.
		• The Tender Inviting Authority (TIA) will not be held responsible for any sort of delay or the difficulties faced during the submission of bids online by the bidders due to local issues.
		• The uploaded tender documents become readable only after the tender opening by the authorized bid openers.
		• Upon the successful and timely submission of bids, the portal will give a successful bid submission message & a bid summary will be displayed with the bid no. and the date & time of submission of the bid with all other relevant details.
		<ul> <li>Kindly add scanned PDF of all relevant documents in a single PDF file of compliance sheet.</li> </ul>
		<ul> <li>More information useful for submitting online bids on the CPP Portal may be obtained at: <a href="https://etenders.gov.in/eprocure/app">https://etenders.gov.in/eprocure/app</a>.</li> <li>All tender documents including pre-qualification bid, Technical Bid &amp;Financial Bid should be submitted separately in online CPP portal as per the specified format only. Right is reserved to ignore any tender which fails to comply with the above instructions. No manual bid submission will be entertained.</li> </ul>
<u>F)</u>	Marking on Technical Bid	• The bidder eligibility criteria, technical specification and supply of item for this tender is given in Annexure A.
		• The Bidders shall go through the specification and submit the technical bid.
		<ul> <li>The Technical bid should be submitted in the proforma as per Annexure-B in pdf format only through online (e-tender). No manual submission of bid will be entertained.</li> </ul>
		• The technical bid should have a page-wise heading as "Technical Bid" and page no. in all pages with seal and signature of authorized signatory. The total no. of pages should be mentioned at the last page of the documents.
		• The technical bid should consist of bidder eligibility criteria details and all technical details along with catalogue/ pamphlet which will give a detailed description of product with technical data sheet so that technical compliance can be verified.
<u>G)</u>	Marking on Price Bid	• Financial bid (BoQ) should be submitted in the prescribed proforma format as per Annexure-C in xls format through e-tender only. No manual or other form of submission of Financial Bid will not be entertained
L	<u> </u>	

4) **Preparation of Tender**: The bidders should submit the bids in two bid system as detailed below.

#### Bid I \_Technical Bid

The technical bid should consist of bidder eligibility criteria and technical specification compliance sheet as per Annexure-B.

#### Bid II \_Price Bid

The price bid should be submitted in excel format (BoQ) as per the proforma (Annexure C) uploaded in the e-Tender web site. The Quoted price should be for supply and installation of the item and inclusive of all cost and statutory levies at IIT Madras.

#### 5) Price:

- a) The price should be quoted only in INR net per unit (after breakup) and must include all packing, transit insurance and delivery charges to the Department of Chemistry.
- b) The rate quoted shall be all inclusive of all taxes and no extra payment will be made other than statutory revisions as per the terms and conditions stipulated in this contract document.
- c) The percentage of tax & duties should be clearly indicated separately. IIT Madras is eligible for custom duty (5.5%). Relevant certificates will be issued wherever necessary.
- d) The offer/bids should be submitted through online only in two bid system i.e. Technical Bid and Financial Bid separately.

#### 6) Tenderer shall submit along with this tender:

- (i) Proof of having ISO or other equivalent certification given by appropriate authorities.
- (ii) Name and full address of the Banker and their swift code and PAN No. and GSTIN number.
- (iii) GST registration proof showing registration number, area of registration etc.
- (iv) All of your future correspondences including Invoices should bear the GST No. and Area Code.

#### 7) Terms of Delivery:

Supplier will be fully responsible for the safe carriage, Installation/Commissioning of goods up to the Department of Chemistry., IIT Madras or named place as per PO, Insurance coverage will be in the scope of the supplier.

The tenderer should indicate clearly the time required for delivery of the item (subject to the approval of the Executive Committee-IIT-Madras). In case there is any deviation in the delivery schedule, liquidated damages clause will be enforced or penalty for the delayed supply period will be levied.

In the event of delay or non-supply of materials/execution of Contract beyond the date of delivery/completion of job. The penalty will be levied @1% per week of delay subject to a max of 10% of the value of purchase order and if the delay is more than accepted time frame by IIT M, the PO would be partially or fully cancelled and liquidated damages will be enforced accordingly.

#### 8) Period for which the offer will remain open:

The Tender shall remain open for acceptance/validity till: 120 days from the date of opening of the tender. However, the day up to which the offer is to remain open being declared closed holiday for the Indian Institute of Technology Madras, the offer shall remain open for acceptance till the next working day.

#### 9) **EMD**:

The EMD of **Rs. 60, 000** to be transferred to the account details mentioned in Annexure D and proof should be enclosed in the Technical Bid. Any offer not accompanied with the EMD shall be rejected summarily as non-responsive.

The EMD of the unsuccessful bidders shall be returned within 30 days of the end of the bid validity period. The same shall be forfeited, if the tenderers withdraw their offer after the opening during the bid validity period. The Institute shall not be liable for payment of any interest on EMD.

EMD is exempted for Micro and Small Enterprises (MSE) as defined in MSE Procurement Policy issued by Department of Micro, Small and Medium Enterprises (MSME) and Startups as recognized by Department of Industrial Policy & Promotion (DIPP). (MSE/MSME/DIPP PROOF should be enclosed in the cover containing technical bid).

#### 10) **Performance Security: -**The successful bidder should submit Performance Security for an amount of 3% of the value of the contract/supply. The Performance Security may be furnished in the form of an Account Payee DD, FD Receipt in the name of "The Registrar, IIT Madras" from any scheduled commercial bank or Bank Guarantee from any scheduled commercial bank in India. The performance security should be furnished within 14 days from the date of the purchase order. Performance Security in the form of Bank Guarantee: - In case the successful bidder wishes to submit Performance Security in the form of Bank Guarantee, the Bank Guarantee should be routed directly to IIT Madras from the Bank. The Bank Guarantee should remain valid for a period of sixty days beyond the date of completion of all contractual obligations of the supplier including the warranty obligations. For the same tender, either the OEM or the authorized dealer/service provider can only quote. But both 11) of them cannot quote separately for the same tender. The offers/bids should be sent only for a item/Equipments of latest version that is available in the market **12**) and supplied to a number of customers. A list of customers in India with details must accompany the quotations. Quotations for a prototype machine will not be accepted 13) Original catalogue (not any photocopy) of the quoted model duly signed by the principals must accompany the quotation in the Technical bid. Compliance or Confirmation report with reference to the specifications and other terms & conditions **14**) should also be obtained from the principal/OEM. **15**) **Risk Purchase Clause** In the event of failure of supply of the item/equipment within the stipulated delivery schedule, the purchaser has all the right to purchase the item/equipment from other sources on the total risk of the supplier under risk purchase clause. **16**) **Payment:** No Advance payment will be made. However, 90% Payment against Delivery and 10% after installation are agreed to wherever the installation is involved. Advance Payment: No advance payment is generally admissible. In case a specific percentage of advance payment is required, the Vendor has to submit a Bank Guarantee from a scheduled commercial bank in India equivalent to the amount of advance payment. **17**) **On-site Installation:** The equipment/item or Machinery has to be installed or commissioned by the successful bidder within the number of days (as prescribed by PI) from the date of receipt of the item at the site of IIT Madras. 18) Warranty/Guarantee: The offer should clearly specify the warranty or guarantee period for the machinery/equipment. Any extended warranty offered for the same has to be mentioned separately (For more details please refer our Technical Specifications). \*\* Note: PO which involves installation, warranty/guarantee shall be applicable from date of installation. **19**) **Acceptance and Rejection:** Failure to comply with any of the instructions stated in this document or offering unsatisfactory explanations for non-compliance will likely to lead to rejection of offers. I.I.T. Madras has the right to accept the whole or any part of the Tender or portion of the

	quantity offered or reject it in full without assigning any reason.			
20)	Debarment from Bidding:			
	In case of breach of Terms & Conditions, Bidder may be suspended from being eligible for bidding in any contract with the IIT Madras up to 2 Years [as per Rule 151(iii) of GFR] from the date of Tender.			
21)	Disputes and Jurisdiction:			
	Settlement of Disputes: Any dispute, controversy or claim arising out of or in connection with this PO including any question regarding its existence, validity, breach or termination, shall in the first instance be attempted to be resolved amicably by both the Parties. If attempts for such amicable resolution fails or no decision is reached within 30 days whichever is earlier, then such disputes shall be settled by arbitration in accordance with the Arbitration and Conciliation Act, 1996. Unless the Parties agree on a sole arbitrator, within 30 days from the receipt of a written request by one Party from the other Party to so agree, the arbitral panel shall comprise of three arbitrators. In that event, the supplier will nominate one arbitrator and the Project Coordinator of IITM shall nominate on arbitrator. The Dean IC&SR will nominate the Presiding Arbitrator of the arbitral tribunal. The arbitration proceeding shall be carried out in English language. The cost of arbitration and fees of the arbitrator(s) shall be shared equally by the Parties. The seat of arbitration shall be at IC&SR IIT Madras, Chennai.  a. The Applicable Law: The Purchase Order shall be construed, interpreted and governed by the			
	Laws of India. Court at Chennai shall have exclusive jurisdiction subject to the arbitration			
	clause.			
	b. Any legal disputes arising out of any breach of contact pertaining to this tender shall be settled in the court of competent jurisdiction located within the city of Chennai in Tamil Nadu.			
22)	<b>Force Majeure:</b> The Supplier shall not be liable for forfeiture of its performance security, liquidated damages or termination for default, if and to the extent that, it's delay in performance or other failure to perform its obligations under the Contract is the result of an event of Force Majeure.			
	For purposes of this Clause, "Force Majeure" means an event beyond the control of the Supplier and not involving the Supplier's fault or negligence and not foreseeable. Such events may include, but are not limited to, acts of the Purchaser either in its sovereign or contractual capacity, wars or revolutions, fires, floods, epidemics, quarantine restrictions and freight embargoes.			
	If a Force Majeure situation arises, the Supplier shall promptly notify the Purchaser in writing of such conditions and the cause thereof. Unless otherwise directed by the Purchaser in writing, the Supplier shall continue to perform its obligations under the Contract as far as is reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the Force Majeure event.			
23)	Eligibility Criteria:			
,	> As per the Government of India Order, only "Class - I Local Suppliers" and "Class - II Local Suppliers" can participate in this tender.			
	Bidder should confirm their acceptance that they comply with the provisions with report to "Guidelines for eligibility of a bidder from a country which shares a land border with India as detailed at Annexure-F. The bidder should submit Certificate for "Bidder from/Not from Country sharing Land border with India & Registration of Bidder with Competent Authority" as per Order of DoE F.No.6/18/2019-PPD dated 23.07.2020 as mentioned.			
24)	Preference to "class I Local Suppliers": preference will be given to "class 1 local suppliers" (subject to class -I local supplier's quoted price falling within the margin of purchase preference ) as per public procurement (preference to make in India) order 2017 .O.M No P- 45021/2/2017 – pp(BE - 11) dt			
	04/06/2020 subject to the conditions that the "class 1 Local Supplier" should agree to supply goods /			

provide service at L1 rate and furnish a certificate with the technical bid document that the goods/service provided by them consists local content equal to or more than 50%.( certificate from Chartered Accountant in case value of contract exceeds Rs 10 crore).

- > 'Class I local supplier' means a supplier or service provider whose goods, services or works offered for procurement consists of local content equal to or more than 50% as defined under the above said order. Declaration to be provided as per Annexure-E per item/service/work.
- ➤ 'Class II local supplier' means a supplier or service provider whose goods, services or works offered for procurement consists of local content equal to 20% but less than 50% as defined under the above said order. Declaration to be provided as per Annexure-E per item/service/work.
- ➢ 'Margin of purchase preference': The margin of purchase preference shall be 20%. The Definition of the margin of purchase preference is defined in the Govt. of India Order No: P-45021/12/2017-PP (BE-II) Dt.4th June, 2020) Order 2017. As per the Government of India Order "Margin of Purchase Preference" means the maximum extent to which the price quoted by a "Class-I local supplier" may be above the L1 for the purpose of purchase preference.

\*\*Note: Local content percentage to be calculated in accordance with the definition provided at clause 2 of revised public procurement preference to Make in India Policy vide GoI Order no. P-45021/2/2017-PP (B.E.-II) dated 15.06.2017 (subsequently revised vide orders dated 28.05.2018, 29.05.2019and 04.06.2020) MOCI order No. 45021/2/2017-PP (BE II) Dt.16th September 2020 & P-45021/102/2019-BE-II-Part(1) (E-50310) Dt.4th March 2021

# **Evaluation of Bids**

Bid evaluation will take place in two stages.

#### Stage I Technical Bid evaluation

All bidders who have fully complied with bidder eligibility criteria I, II and technical evaluation (Annexure A) will only be considered for opening of price bid.

#### **Stage II: Price Bid Evaluation**

The price bid evaluation will be based on price quoted by the bidder. The rate quoted for **GLOVE BOX** unit will alone be taken up for arrival of Lowest Bid (L1) value.

- 26) Selection of successful bidder and Award of Order
  - The order will be directly awarded to the technically qualified bidder as per the condition in para 3A of DIPP, MoCI Order No. 45021/2/2017-PP (BE II) dated 16th September 2020.
- All information including selection and rejection of technical or financial bids of the prospective bidders will be communicated through e-Tender portal. In terms of Rule 173(iv) of General Financial Rule 2017, the bidder shall be at liberty to question the bidding conditions, bidding process and/or rejection of bids.
- The tenderer shall certify that the tender document submitted by him / her are of the same replica of the tender document as published by IIT Madras and no corrections, additions and alterations made to the same. If any deviation found in the same at any stage and date, the bid / contract will be rejected / terminated and actions will be initiated as per the terms and conditions of the contract.
- Due to Covid-19 pandemic pre-bid meeting will be conducted through online. Clarification to the queries and doubts raised by the bidders will be issued as a corrigendum/addendum in the e-tenders portal.
- Due to Covid-19 pandemic the bidders will not be entertained to participate in opening of Bids. Since the tender is e-tender, the opening of the bids may be checked using the respective logins of the bidders.

# **ACKNOWLEDGEMENT**

It is hereby acknowledged that I/We have gone through all the points listed under "Specification, Guidelines, Terms and Conditions" of tender document. I/We totally understand the terms and conditions and agree to abide by the same.

SIGNATURE OF TENDERER ALONG WITH SEAL OF THE COMPANY WITH DATE

#### Bidder Eligibility Criteria and Technical Specification for GLOVE BOX

Tender No. CY/PRAD/05/IOE23/GLOVEBOX

#### Bidder Eligibility Criteria – I (Public Procurement – Preference to Make in India)

Only 'Class-I local suppliers' and 'Class-II local suppliers', as defined under DIPP, MoCI Order No. P-45021/2/2017-PP (BE-II) dated 16<sup>th</sup> September 2020 and other subsequent orders issued therein.

#### Bidder Eligibility Criteria - II

The bidder/OEM should have supplied at least 5 similar Glove Box to IITs, NITs, IISERs, CSIR Labs or other Govt. R&D organizations in the last 5 years. PO copies or installation certificates along with contact details of end users need to be submitted as proof of supply. IIT Madras reserves its right to verify the claims.

# **III. Technical Specification For GLOVE BOX**

Following are the desired specifications for Glove Box:

S1.No.	Description
	Enclosure:
1	The working space of each glove box should be at least 850 - 890 mm in height, 1700 to 1850 mm in length and 750 mm to 800 in depth.
2	The window materials should be impact-resistant polycarbonate that is at least 10 mm thick.
3	Main body must be SS304 or SS316 brushed stainless steel, at least 2.5 mm thick.
4	The trays, rails and other components in the ante-chambers should also be of 304 grade or 316 grade or similar corrosion/chemical resistant grades of brushed stainless steel.
5	The external should either be a powder-coated or a spray paint finish.
6	We strongly prefer a system in which the space underneath the glove box is empty.
7	Need a modular system that can be expanded further. The side-panels must be removable to accommodate future expansions.
	Programmatic Logic Control:
1	Glove box should be controllable with independent and fully integrated Siemens programmatic logic control (PLC), with a touch panel interface
2	The touch panel interface should serve as a central control unit for all glove box functions and procedures.

3	All glove box functions should be accessible via the touch panel.
4	Graphical display of the box pressure, O <sub>2</sub> and moisture levels should be available in the touch panel
	interface.
5	Automatic box purge should be possible via PLC.
6	PLC should trigger an automatic box purge either due to high O <sub>2</sub> or moisture or both in the glove box or an
0	automatic timer option to trigger box purge at a pre-set time for a pre-set duration.
	automatic time option to urgger box purge at a pre-set time for a pre-set duration.
7	Touch panel implementations showing this should be provided. A copy of relevant documentation from the
	user manual should also be provided.
8	Gas (argon or nitrogen) flow rate of 200 L/min or greater during purging should be possible.
9	The O <sub>2</sub> and moisture trigger set-point range for automatic box purging should be between 10-999 ppm.
	Touch panel implementations showing this should be provided. A copy of relevant documentation from the
	user manual should also be provided
	Purifier:
1	Single Column Gas purification system 7-inch Siemens touch screen HMI, remote and graphical PLC
	controller with auto-regeneration
2	Glove box should have at least one independent purifier capable of purifying the glove box ambient to
	attain a purity of <1 ppm H <sub>2</sub> O and O <sub>2</sub> .
3	The removable capacity should be a minimum of 41 -45 L for oxygen and at least 1400 to 1600 grams for
	moisture. Specification sheets or data sheets attesting to this must be provided.
4	
4	The purifier should be fully regenerable with an automatic/programmed control using forming gas (10% H <sub>2</sub> or lower) or Ar or N <sub>2</sub> .
	of lower) of Ar or N <sub>2</sub> .
5	The gas circulation blower should be capable of a circulation rate of at least 88 to 100 m <sup>3</sup> /hour. The
	maximum and minimum circulation rates of the blower should be provided and should work without any
	heat exchanger.
6	The blower speed should be dynamically controlled via program logic based on the moisture and oxygen
	content in the glove box, to make the blower operation power efficient. Implementation diagrams or
	specifications that prove this is possible must be provided.
7	The purifier loop must have at least two H14 dust filters (HEPA or ULPA filters) one for filtering inlet
	gas (nitrogen or argon) and one for filtering the box ambient before it goes out to the gas circulation system.
0	Oil bubblers should NOT be used in any of the gas circulation lines. The mechanism for pressure regulation
8	should be clearly mentioned.
	SHOULG DE CIEGITY HICHUDIEG.

9	NO component in the gas circulation line (except for the vacuum pumps) should use oil or oil containing		
	parts.		
10	Eco Mode Operation function		
	Automated Activation: Yes/No		
	Time of Day for Automated activation: HH:MM: SS		
	Blower Speed Reduction: Yes/NO		
	Reduced speed set: option with between 10-100%		
	Max. H <sub>2</sub> O/O <sub>2</sub> at set RPM reduction: such as 10 PPM		
	Switch Off Vacuum pump purifier: Yes/No		
	Switch off Vacuum pumps antechambers: Yes/NO		
	Stopping time for Vacuum pumps: Minutes		
	Switch off Box-light: Yes/No		
	Touch panel implementations showing this should be provided. A copy of relevant documentation		
	from the user manual should also be provided.		
11	Auto purge with time sequence or ppm of O <sub>2</sub> and H <sub>2</sub> O		
	Touch panel implementations showing this should be provided. A copy of relevant documentation from the		
	user manual should also be provided.		
	Sensors:		
1	A solid-state/Electrochemical oxygen sensor capable of measuring oxygen levels from 0.1 ppm to 1000		
	ppm should be provided with box.		
2	A solid-state moisture sensor capable of measuring moisture levels from 0.1 ppm to 3000 ppm should be		
	provided with box.		
	Box pressure:		
1	Box pressure should be controllable automatically (via programmatic logic) within a pressure range of -15		
	to +15 mbar.		
2	The desired pressure should be settable via the touch panel interface. Touch panel implementations showing		
	this should be provided. A copy of relevant documentation from the user manual should also be provided		
	Gloves and Glove Port Covers:		
1	There should be 4 POM (polypropylene is preferred) glove ports for each box and butyl gloves should be		
	provided for these glove ports.		
2	The size of each glove port should be at least 9" in dia		
3	The glove ports should be O-ring sealed against the gloves.		
4	Must include at least one glove port cover.		
5	The thickness of the butyl gloves should be a minimum of 0.4 mm		
	Automatic Large Antechamber:		
1	The box must have one large ante-chamber for sample transfer.		

2	The ante-chamber should be cylindrical with a diameter of at least 400 mm and a length of at ~600 mm.
3	The doors should preferably be with a swing-type hydraulic-assisted opening mechanism to conserve
	working space.
4	There should also be a tray preferably mounted on telescopic rails, which can be slid back and forth. The
	tray should facilitate transfer for tools and chemicals.
5	The chamber must have an Automatic PLC controlled evacuate and purge system with pressure gauge.
6	Bigger antechamber should provide with heating up to 150 °C with independent controller.
	Mini antechambers:
1	The box must have one mini ante-chamber for sample transfer.
2	The ante-chamber should be at least 150 mm in diameter and 400 mm in length.
3	The ante-chamber should have a tray to enable sample transfer.
4	The chamber must have a manual pump and purge system: with pressure gauge, manual valve and
	connection to vacuum pump.
5	The ante-chamber should have a door that can seal the ante-chamber for evacuation.
	Upgradable option should be there for freezer -30 $^{\circ}\mathrm{C}$ and also vendor should provide minimum
	Three installation details of Glove Box integrated with freezer.
	Feedthroughs
1	The box should have at least 4 KF-40 feedthroughs. These can be connected to liquid, electrical or vacuum
	feedthroughs. The details of placement can be discussed at the time of ordering
2	The system must have at least 1 electrical feedthrough with 15 A connector that are compatible with 220 V
	– 240 V supply.
	Double stage rotary vane 20 m³/H VACUUM PUMP with oil mist filter
	System control:
1	Glove box should be PLC controlled with Color touch panel operation of glove box parameters with
	features of circulation control, pressure control, regeneration control and monitoring of pressure, oxygen
	and moisture. Each function should be clearly displayed on touch panel. Alarms and reminders are required
	for maintenance and parts. Activation at user-set timings
2	With Upgrade facility for 24/7 remote monitoring of glove box parameters and provision forsending alerts
	and notifications about upcoming service schedules. Must be freely downloadable from the google play
	store /app store and the chemical calculation function
	Others:
1	There must be a lamp inside, preferably LED. There must be a switch on the outside of the body or
	touchscreen to turn the light on/off.
2	The circulation system should make it possible to have positive pressure regulation without vacuum pump
3	A foot pedal for controlling box pressure should be provided.
4	At least two height-adjustable stainless-steel shelves of at least 1000 mm in length and at least 200 mm in
	depth should be provided. These should be centrally located so that any chemicals or tools are accessible

	from glove ports.
5	All electrical connections should comply with line power specifications in India. Single phase voltage range
	is 220-240 Vac and the three-phase voltage range is 415 - 440 Vac. The line frequency is 50Hz.
	Acceptance Tests:
1	IIT Madras will expect acceptance tests, post installation. These can be recorded in the presence of
	representatives of the OEM. Inability to pass these tests will be a counted as a technical failure and breach
	of contract.
2	IIT Madras has complete rights technically reject or accept based on user feedback and reference.
3	Maintain <1 ppm of H2O and O2 for 24-hour period.
4	Demonstrate automated routines for catalyst regeneration
5	Demonstrate automated routines for maintaining target pressure.
	Other Terms and Conditions:
1	Comprehensive warranty for 3 years.
2	Maintenance Contract: Operational services should be provided for 2 years after warranty.
3	Software updates, if any, to be provided free of cost.
4	Installation and training to be provided.
5	Instrument to operate smoothly in Indian conditions.

### TECHNICAL BID PROFORMA

Tender No. CY/PRAD/05/IOE23/GLOVEBOX Item Name: GLOVE BOX

# 1.0 Bidder Eligibility Criteria:

I	Bidder Eligibility Criteria-I (Public Procurement – Preference to Make in India)	Class I / Class II	Local Content value	Reference, Page No.
I	Only 'Class-I local suppliers' and 'Class-II local suppliers', as defined under DIPP, MoCI Order No. P-45021/2/2017-PP (BE II) dated 16 <sup>th</sup> September 2020 and other subsequent orders issued therein.			
2.0	Bidder Eligibility Criteria-II	Compliance (Yes/No)	Reference Page No.	Remarks, If any
1	The bidder/OEM should have supplied at least 5 similar Glove Box to IITs, NITs, IISERs, CSIR Labs or other Govt. R&D organizations in the last 5 Years, PO copies or installation certificates along with contact details of end users need to be submitted as proof of supply. IIT Madras reserves its right to verify the claims.			

# 3.0 Technical Compliance:

Following are the desired specifications for Glove Box:

S1. No	Description	Compliance (Yes/No)	Reference Page No
	Enclosure:		
1	The working space of each glove box should be at least 850 - 890 mm in		
	height, 1700 to 1850 mm in length and 750 mm to 800 in depth.		
2	The window materials should be impact-resistant polycarbonate that is at least		
	10 mm thick.		
3	Main body must be SS304 or SS316 brushed stainless steel, at least 2.5 mm		
	thick.		
4	The trays, rails and other components in the ante-chambers should also be of		
	304 grade or 316 grade or similar corrosion/chemical resistant grades of		
	brushed stainless steel.		

5	The external should either be a powder-coated or a spray paint finish.		
6	We strongly prefer a system in which the space underneath the glove box is		
	empty.		
7	Need a modular system that can be expanded further. The side-panels must be		
	removable to accommodate future expansions.		
	Programmatic Logic Control:		
1	Glove box should be controllable with independent and fully integrated		
	Siemens programmatic logic control (PLC), with a touch panel interface		
2	The touch panel interface should serve as a central control unit for all glove		
	box functions and procedures.		
3	All glove box functions should be accessible via the touch panel.		
3	An grove box functions should be accessible via the touch panel.		
4	Graphical display of the box pressure, O <sub>2</sub> and moisture levels should be		
	available in the touch panel interface.		
5	Automatic box purge should be possible via PLC.		
6	PLC should trigger an automatic box purge either due to high O <sub>2</sub> or moisture		_
	or both in the glove box or an automatic timer option to trigger box purge at a		
	pre-set time for a pre-set duration.		
7	Touch panel implementations showing this should be provided. A copy of		
	relevant documentation from the user manual should also be provided.		
8	Gas (argon or nitrogen) flow rate of 200 L/min or greater during purging		
	should be possible.		
9	The O <sub>2</sub> and moisture trigger set-point range for automatic box purging should		
	be between 10-999 ppm. Touch panel implementations showing this should be provided. A copy of relevant documentation from the user manual should		
	also be provided		
	Purifier:		
1	Single Column Gas purification system 7-inch Siemens touch screen HMI,		
	remote and graphical PLC controller with auto-regeneration		
2	Glove box should have at least one independent purifier capable of purifying		=
	the glove box ambient to attain a purity of <1 ppm H <sub>2</sub> O and O <sub>2</sub> .		
3	The removable capacity should be a minimum of 41 -45 L for oxygen and at		
	least 1400 to 1600 grams for moisture. Specification sheets or data sheets		
	I .	1	

	attesting to this must be provided.	
4	The purifier should be fully regenerable with an automatic/programmed	
	control using forming gas (10% H <sub>2</sub> or lower) or Ar or N <sub>2</sub> .	
5	The gas circulation blower should be capable of a circulation rate of at least	
	88 to 100 m <sup>3</sup> /hour. The maximum and minimum circulation rates of the	
	blower should be provided and should work without any heat exchanger.	
6	The blower speed should be dynamically controlled via program logic based	
	on the moisture and oxygen content in the glove box, to make the blower	
	operation power efficient. Implementation diagrams or specifications that	
	prove this is possible must be provided.	
7	The purifier loop must have at least two H14 dust filters (HEPA or ULPA	
	filters) one for filtering inlet gas (nitrogen or argon) and one for filtering the	
	box ambient before it goes out to the gas circulation system.	
8	Oil bubblers should NOT be used in any of the gas circulation lines. The	
	mechanism for pressure regulation should be clearly mentioned.	
9	NO component in the gas circulation line (except for the vacuum pumps)	
	should use oil or oil containing parts.	
10	Eco Mode Operation function	
	Automated Activation: Yes/No	
	Time of Day for Automated activation: HH:MM: SS	
	Blower Speed Reduction: Yes/NO	
	Reduced speed set: option with between 10-100%	
	Max. H <sub>2</sub> O/O <sub>2</sub> at set RPM reduction: such as 10 PPM	
	Switch Off Vacuum pump purifier: Yes/No	
	Switch off Vacuum pumps antechambers: Yes/NO	
	Stopping time for Vacuum pumps: Minutes	
	Switch off Box-light: Yes/No	
	Touch panel implementations showing this should be provided. A copy of	
	relevant documentation from the user manual should also be provided.	
11	Auto purge with time sequence or ppm of O <sub>2</sub> and H <sub>2</sub> O	
	Touch panel implementations showing this should be provided. A copy of	

	relevant documentation from the user manual should also be provided.	
	Sensors:	
1	A solid-state/Electrochemical oxygen sensor capable of measuring oxygen	
	levels from 0.1 ppm to 1000 ppm should be provided with box.	
	A solid state maisture sensor complete of massessing and interest from 0.1	
2	A solid-state moisture sensor capable of measuring moisture levels from 0.1	
	ppm to 3000 ppm should be provided with box.	
	Box pressure:	
1	Box pressure should be controllable automatically (via programmatic logic)	
	within a pressure range of -15 to +15 mbar.	
2	The desired pressure should be settable via the touch panel interface. Touch	
	panel implementations showing this should be provided. A copy of relevant	
	documentation from the user manual should also be provided	
	Gloves and Glove Port Covers:	
1	There should be 4 POM (polypropylene is preferred) glove ports for each box	
	and butyl gloves should be provided for these glove ports.	
2	The size of each glove port should be at least 9" in dia	
3	The glove ports should be O-ring sealed against the gloves.	
4	Must include at least one glove port cover.	
5	The thickness of the butyl gloves should be a minimum of 0.4 mm	
	Automatic Large Antechamber:	
1	The box must have one large ante-chamber for sample transfer.	
2	The ante-chamber should be cylindrical with a diameter of at least 400 mm	
	and a length of at ~600 mm.	
3	The doors should preferably be with a swing-type hydraulic-assisted opening	
	mechanism to conserve working space.	
4	There should also be a tray preferably mounted on telescopic rails, which can	
	be slid back and forth. The tray should facilitate transfer for tools and	
	chemicals.	
5	The chamber must have an Automatic PLC controlled evacuate and purge	
	system with pressure gauge.	
6	Bigger antechamber should provide with heating up to 150 °C with	
	independent controller.	
	Mini antechambers:	
1	The box must have one mini ante-chamber for sample transfer.	
2	The ante-chamber should be at least 150 mm in diameter and 400 mm in	
	length.	

The chamber must have a manual pump and purge system: with pregauge, manual valve and connection to vacuum pump.  The ante-chamber should have a door that can seal the ante-chamber evacuation.  Upgradable option should be there for freezer -30 °C and also we should provide minimum Three installation details of Glove Bountegrated with freezer.  Feedthroughs  The box should have at least 4 KF-40 feedthroughs. These can be controling to liquid, electrical or vacuum feedthroughs. The details of placement discussed at the time of ordering  The system must have at least 1 electrical feedthrough with 15 A controling that are compatible with 220 V – 240 V supply.  Double stage rotary vane 20 m³/H VACUUM PUMP with oil manual system control:  Glove box should be PLC controlled with Color touch panel operating glove box parameters with features of circulation control, pressure of the stage of the system control of the control of the control of the system control of the control	er for endor x onnected
The ante-chamber should have a door that can seal the ante-chamber evacuation.  Upgradable option should be there for freezer -30 °C and also we should provide minimum Three installation details of Glove Bountegrated with freezer.  Feedthroughs  The box should have at least 4 KF-40 feedthroughs. These can be controling to to liquid, electrical or vacuum feedthroughs. The details of placemed discussed at the time of ordering  The system must have at least 1 electrical feedthrough with 15 A controling that are compatible with 220 V - 240 V supply.  Double stage rotary vane 20 m³/H VACUUM PUMP with oil minutegrated with Color touch panel operation.	rendor x onnected
<ul> <li>evacuation.         Upgradable option should be there for freezer -30 °C and also we should provide minimum Three installation details of Glove Boot integrated with freezer.     </li> <li>Feedthroughs</li> <li>The box should have at least 4 KF-40 feedthroughs. These can be control to liquid, electrical or vacuum feedthroughs. The details of placemed discussed at the time of ordering     </li> <li>The system must have at least 1 electrical feedthrough with 15 A contract that are compatible with 220 V - 240 V supply.         Double stage rotary vane 20 m³/H VACUUM PUMP with oil minimum System control:     </li> <li>Glove box should be PLC controlled with Color touch panel operation.</li> </ul>	rendor x onnected
Upgradable option should be there for freezer -30 °C and also veshould provide minimum Three installation details of Glove Bountegrated with freezer.  Feedthroughs  The box should have at least 4 KF-40 feedthroughs. These can be control to liquid, electrical or vacuum feedthroughs. The details of placemed discussed at the time of ordering  The system must have at least 1 electrical feedthrough with 15 A control that are compatible with 220 V – 240 V supply.  Double stage rotary vane 20 m³/H VACUUM PUMP with oil minimum System control:  Glove box should be PLC controlled with Color touch panel operations.	onnected
should provide minimum Three installation details of Glove Bountegrated with freezer.  Feedthroughs  The box should have at least 4 KF-40 feedthroughs. These can be control to liquid, electrical or vacuum feedthroughs. The details of placemed discussed at the time of ordering  The system must have at least 1 electrical feedthrough with 15 A control that are compatible with 220 V – 240 V supply.  Double stage rotary vane 20 m³/H VACUUM PUMP with oil minutegraphs.  System control:  Glove box should be PLC controlled with Color touch panel operations.	onnected
<ul> <li>integrated with freezer.</li> <li>Feedthroughs</li> <li>The box should have at least 4 KF-40 feedthroughs. These can be c to liquid, electrical or vacuum feedthroughs. The details of placemed discussed at the time of ordering</li> <li>The system must have at least 1 electrical feedthrough with 15 A c that are compatible with 220 V – 240 V supply.</li> <li>Double stage rotary vane 20 m³/H VACUUM PUMP with oil missing System control:</li> <li>Glove box should be PLC controlled with Color touch panel operations.</li> </ul>	onnected
Feedthroughs  The box should have at least 4 KF-40 feedthroughs. These can be control:  The box should have at least 4 KF-40 feedthroughs. These can be control:  The box should have at least 4 KF-40 feedthroughs. The details of placement discussed at the time of ordering  The system must have at least 1 electrical feedthrough with 15 A control that are compatible with 220 V – 240 V supply.  Double stage rotary vane 20 m³/H VACUUM PUMP with oil missing system control:  Glove box should be PLC controlled with Color touch panel operations.	
1 The box should have at least 4 KF-40 feedthroughs. These can be c to liquid, electrical or vacuum feedthroughs. The details of placemed discussed at the time of ordering  2 The system must have at least 1 electrical feedthrough with 15 A c that are compatible with 220 V – 240 V supply.  Double stage rotary vane 20 m³/H VACUUM PUMP with oil missing System control:  1 Glove box should be PLC controlled with Color touch panel operations.	
to liquid, electrical or vacuum feedthroughs. The details of placemed discussed at the time of ordering  The system must have at least 1 electrical feedthrough with 15 A countries that are compatible with 220 V – 240 V supply.  Double stage rotary vane 20 m³/H VACUUM PUMP with oil missing System control:  Glove box should be PLC controlled with Color touch panel operations.	
discussed at the time of ordering  The system must have at least 1 electrical feedthrough with 15 A c that are compatible with 220 V – 240 V supply.  Double stage rotary vane 20 m³/H VACUUM PUMP with oil missingular system control:  Glove box should be PLC controlled with Color touch panel operations.	ent can be
2 The system must have at least 1 electrical feedthrough with 15 A c that are compatible with 220 V – 240 V supply.  Double stage rotary vane 20 m³/H VACUUM PUMP with oil m²  System control:  1 Glove box should be PLC controlled with Color touch panel operations.	
that are compatible with 220 V – 240 V supply.  Double stage rotary vane 20 m³/H VACUUM PUMP with oil m²  System control:  1 Glove box should be PLC controlled with Color touch panel operat	
Double stage rotary vane 20 m³/H VACUUM PUMP with oil mi  System control:  1 Glove box should be PLC controlled with Color touch panel operat	onnector
System control:  1 Glove box should be PLC controlled with Color touch panel operat	
Glove box should be PLC controlled with Color touch panel operat	ist filter
glove box parameters with features of circulation control, pressure	ion of
	control,
regeneration control and monitoring of pressure, oxygen and moistu	ıre. Each
function should be clearly displayed on touch panel. Alarms and re-	minders
are required for maintenance and parts. Activation at user-set timing	gs
2 With Upgrade facility for 24/7 remote monitoring of glove box para	ameters
and provision forsending alerts and notifications about upcoming se	ervice
schedules. Must be freely downloadable from the google play store	/app store
and the chemical calculation function	
Others:	
1 There must be a lamp inside, preferably LED. There must be a swit	ch on the
outside of the body or touchscreen to turn the light on/off.	
2 The circulation system should make it possible to have positive pre	ssure
regulation without vacuum pump	
3 A foot pedal for controlling box pressure should be provided.	
4 At least two height-adjustable stainless-steel shelves of at least 100	0 mm in
length and at least 200 mm in depth should be provided. These should be provided.	ıld be
centrally located so that any chemicals or tools are accessible from	glove
ports.	
5 All electrical connections should comply with line power specificat	
India. Single phase voltage range is 220-240 Vac and the three-phase	ions in

	range is 415 - 440 Vac. The line frequency is 50Hz.
	Acceptance Tests:
1	IIT Madras will expect acceptance tests, post installation. These can be
	recorded in the presence of representatives of the OEM. Inability to pass these
	tests will be a counted as a technical failure and breach of contract.
2	IIT Madras has complete rights technically reject or accept based on user
	feedback and reference.
3	Maintain <1 ppm of H2O and O2 for 24-hour period.
4	Demonstrate automated routines for catalyst regeneration
5	Demonstrate automated routines for maintaining target pressure.
	Other Terms and Conditions:
1	Comprehensive warranty for 3 years.
2	Maintenance Contract: Operational services should be provided for 2 years
	after warranty.
3	Software updates, if any, to be provided free of cost.
4	Installation and training to be provided.
5	Instrument to operate smoothly in Indian conditions.

(Note: It is mandatory for the bidders to provide the compliance statement in tabular column format along with catalogue page number (comply/not comply) for the above points with document proof as required. Failing which bidders will be technically disqualified)

SIGNATURE OF BIDDER ALONG WITH SEAL OF THE COMPANY WITH DATE

# FINANCIAL BID (PROFORMA) - BILL OF QUANTITIES (BOQ)

# Item Name: GLOVE BOX Tender No. CY/PRAD/05/IOE23/GLOVEBOX

It. No	Description of work	Quantity	Units	Basic Rate in INR	GST in Percentage	Total Amount with taxes in INR
1	GLOVE BOX	1	Nos.			
2	Maintenance Contract: Operational services should be provided for 2 years after warranty(optional)	1	Nos.			
	Grand Total					

Total Amount Rupees in words	

Note: Optional Maintenance contract will not be considered for price bid evaluation.



# CENTRE FOR INDUSTRIAL CONSULTANCY & SPONSORED RESEARCH (IC&SR) INDIAN INSTITUTE OF TECHNOLOGY MADRAS CHENNAI 600 036



# ELECTRONIC CLEARING SERVICE (Credit Clearing) / REAL TIME GROSS SETTLEMENT (RTGS) FACILITY FOR RECEIVING PAYMENTS A. Details of Account Holder

Name of the Institution	Indian Institute of Technology - Madras
Complete Contact Address	Industrial Consultancy and Sponsored Research Indian Institute of Technology-Madras, IIT- Madras Campus Post Office, Sardar Patel Road, Guindy, CHENNAI - 600 036
Telephone No./ Fax No.	Tel - 044-2257 8356
E- mail ID of the FO/AO/REG/DIR	dricsr@iitm.ac.in

#### **B. Bank Account Details:**

Institution Account Name (As per Bank	The Registrar, Indian Institute of
Record)	Technology - Madras
Account No.	2722101003872
Account Print Name	IIT F A/C , The Registrar IIT Madras
IFSC CODE	CNRB0002722
Bank Name (in full)	Canara Bank
Branch Name	IIT-Madras Branch
Complete Branch Address	Canara Bank,
	IIT-Madras Branch,
	IIT- Madras Campus Post Office,
	Sardar Patel Road,
	Guindy, CHENNAI - 600 036
MICR No.	600015085
Account Type	Savings Account

Certified that the Institute's account is in an RTGS enabled branch.

I hereby declare that the particulars given above are correct and complete,

Date:

Signature of the competent Authority of the Institution with seal.

# FORMAT FOR AFFIDAVIT OF SELF-CERTIFICATION UNDER PREFERENCE TO MAKE IN INDIA – PER ITEM

Tender Reference Number:		
Name of the item / Service:		
Date: I/WeS/o, D/o, W/o, Resident of		
Hereby solemnly affirm and declare as under:		
That I will agree to abide by the terms and conditions of the Public Procurement (Preference to Make in India) Policy vide GoI Order no. P-45021/2/2017-PP (B.EII) dated 15.06.2017 (subsequently revised vide orders dated 28.05.2018, 29.05.2019 and 04.06.2020) MOCI order No. 45021/2/2017-PP (BE II) Dt.16th September 2020 & P- 45021/102/2019-BE-II-Part (1) (E-50310) Dt.4th March 2021 and any subsequent modifications/Amendments, if any and		
That the local content for all inputs which constitute the said item/service/work has been verified by me and I am responsible for the correctness of the claims made therein.		
Tick (✓) and Fill the Appropriate Category  I/We [name of the supplier] hereby confirm in respect of quoted items thatLocal Content is equal to or more than 50% and come under "Class-I Local Supplier" category.  I/We [name of the supplier] hereby confirm in respect of quoted items		
that Local Content is equal to 20% but less than 50% and come under "Class-II Local Supplier" category.		
• The details of the location (s) at which the local value addition is made and the proportionate value of local content in percentage		
Address Percentage of Local content:%		
For and on behalf of(Name of firm/entity)		
Authorized signatory (To be duly authorized by the Board of Directors) <insert and="" contact="" designation="" name,="" no.=""></insert>		
[Note: In case of procurement for a value in excess of Rs. 10 Crores, the bidders shall provide this certificate from statutory auditor or cost auditor of the company (in the case of companies) or from a practicing cost accountant or practicing chartered accountant (in respect of suppliers other than companies) giving the percentage of local content.]		

This letter should be on the letterhead of the quoting firm and should be signed by a competent authority. Non-submission of this will lead to Disqualification of bids.

# Annexure – F

(To be	given on the letter head of the bidder)
No	Dated:
	<u>CERTIFICATE</u>
	(Bidders from India)
I have read the clause regarding restr border with India and hereby certify t	ictions on procurement from a bidder of a country which shares a land hat I am not from such a country.
	OR (whichever is applicable)
(Bidders from	Country which shares a land border with India)
border with India and hereby certify registered with the Competent Author	ictions on procurement from a bidder of a country which shares a land that I from (Name of Country) and has been brity. I also certify that I fulfil all the requirements in this regard and is ence of valid registration by the Competent Authority is to be attached)
Place: Date:	Signature of the Tenderer Name & Address of the Tenderer with Office Stamp